



EVX 12380

12V 38.0Ah

EVX 12380 is designed specially for electric vehicles, such as electric golf cart, electric wheelchair, mower, dust collector...etc. It has high cycling life, high efficiency and long service life.



Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	38Ah @ 20hr-rate to 1.75V per cell @25 °C (77°F)
Weight	Approx.12.0kg(26.4 lbs)
Maximum Discharge Current	400A(5sec)
Internal Resistance	Approx. 8.0mΩ
Operating Temperature Range	Discharge: -15°C~50°C (5°F~122°F) Charge: -15~40°C (5°F~104°F) Storage: -15°C~40°C (5°F~104°F)
Nominal Operating Temperature Range	25°C±3°C(77°F±5°F)
Float Charging Voltage	13.5 to 13.8 VDC/unit Average at 25°C(77°F)
Recommended Maximum Charging Current Limit	11.4A
Equalization and Cycle Service	14.4 to 15.0 VDC/unit Average at 25°C(77°F)
Self Discharge	CSB Batteries can be stored for more than 6 months at 25°C(77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	Bolt & Nut
Container Material	-ABS (UL94-HB)*Flammability resistance of UL94-V0 can be available upon request.



MH14533(N)



ISO9001

No :041005117



ISO 14001


NO.UM 1-12-0045

CSB-manufactured batteries are UL-recognized components under UL924 and UL1989.

CSB is also certified by ISO 9001 and ISO 14001.

Dimensions

unit: (MM)



Constant Current Discharge Characteristics Unit:A (25°C , 77°F)


F.V/Time	30MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	38.60	22.70	17.30	14.00	10.10	8.04	6.75	4.56	3.79	2.08
1.67V	37.20	22.20	17.10	13.80	10.00	8.02	6.69	4.46	3.67	1.96
1.70V	36.60	22.00	17.00	13.70	9.97	8.01	6.67	4.41	3.62	1.91
1.75V	35.50	21.50	16.60	13.50	9.82	7.88	6.56	4.35	3.56	1.90
1.80V	34.50	21.10	16.30	13.20	9.68	7.74	6.45	4.29	3.51	1.85
1.85V	33.40	20.60	16.00	13.00	9.53	7.60	6.35	4.22	3.45	1.82

Constant Power Discharge Characteristics Unit:W (25°C , 77°F)


F.V/Time	30MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	463.00	273.00	208.00	168.00	121.00	96.50	81.10	54.80	45.40	24.80
1.67V	446.00	267.00	205.00	166.00	120.00	96.20	80.30	53.50	44.00	23.50
1.70V	439.00	264.00	204.00	164.00	120.00	96.10	79.90	52.90	43.40	22.90
1.75V	426.00	258.00	200.00	162.00	118.00	94.50	78.70	52.20	42.80	22.60
1.80V	414.00	253.00	196.00	159.00	116.00	92.90	77.40	51.40	42.10	22.20
1.85V	401.00	247.00	192.00	156.00	114.00	91.30	76.20	50.70	41.50	21.80

● All mentioned values are average values.


Trickle (or Float) Service Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use




GP & EVX Series Cycle Service Life



Battery Voltage and Charge Time for Cycle Use



Terminal Voltage (V) and Discharge Time (25°C 77°F)



Charging Procedures

Application	Charge Voltage (V/Cell)			Max. Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C (77°F)	2.45	2.40~2.50	0.3C
Standby	25°C (77°F)	2.275	2.25~2.30	

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.55	1.30
Discharge Current (A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

Sales Office URL: WWW.CSB-BATTERY.COM

CSB BATTERY CO., LTD.
TAIWAN OFFICE
Tel: +886-2-8751-5000
Fax: +886-2-8751-6161
E-mail: service@csb-battery.com.tw

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
SHANGHAI OFFICE
Tel: +86-21-5046-1622, 5046-0833
Fax: +86-21-5064-3314

CSB BATTERY TECHNOLOGIES, INC
USA OFFICE
Tel: +1-817-244-7777/1-8003 CSBUSA(272872)
Fax: +1-817-244-4445
E-mail: csb@csb-battery.com

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
BEIJING OFFICE
Tel: +86-10-6597-8060, 6597-8070
Fax: +86-10-6597-8050
E-mail: chinassls@csb-battery.com

CSB BATTERY OF NETHERLANDS B.V
NETHERLANDS OFFICE
Tel: +31(0) 180 418 140
Fax: +31(0) 180 418 327
E-mail: eurossales@csb-battery.com

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
SHENZHEN OFFICE
Tel: +86-755-88316356 88316488 88316396
Fax: +86-755-88316548
E-mail: she@csb-battery.com.tw